
UNITECH DIGITAL MEDIA ultra professional LED display company



# FLOOD Light

UNITECH DIGITAL MEDIA

# Flood Light

## FEATURES

- Flood Light Series is designed for architectural facede, bridge and so on.
- High Efficiency light output and uniform beam with professional lense.
- Top brand silicone  for better heatconduction, strong temperature withstand and perfect waterproof performance.
- Led color always keep same brightness after long distance power supply.
- The communication between lights are synchronized perfectly under support of Artnet Controller.
- Standard DMX512 control protocol (Max 44frames/second).
- Save 40% power with more efficient power management design.
- Protections: short circuit, over current, over voltage and over temperature.

FL800303
Flood Light



FL960903 – FL1351603 –
FL1702403 – FL2136003
Flood Light



FL1700904 – FL2131604
Flood Light



FL1100603 – FL1700903 – FL2061803 –
FL2403603 – FL2405403 – FL2806003
Flood Light





## SPECIFICATION


| | FL800303 | FL960903 | FL1351603 | FL1702403 | FL2136003 |
|---|---|---|---|---|---|
| Size | 80x80x123mm | 96x96xd110xh150mm | 135x135xd140xh215mm | 170x170xd137xh245mm | 213x213xd190xh345mm |
| Diffuser | Clear Tempered Glass | Clear Tempered Glass | Clear Tempered Glass | Clear Tempered Glass | Clear Tempered Glass |
| Color | White 2700K-5770K/RGB | White 2700K-5770K/RGB | White 2700K-5770K/RGB | White 2700K-5770K/RGB | White 2700K-5770K/RGB |
| Led | High Power LED | High Power LED | High Power LED | High Power LED | High Power LED |
| Led Q.ty | 3 PCS | 9 PCS | 16 PCS | 24 PCS | 60 PCS |
| Beam angle | 10°-15°-22°-30°-50°-66°-83° | | | | |
| Voltage | 24V DC | 85-260V DC | 85-260V DC | 85-260V DC | 85-260V DC |
| Power | 8W | 18W | 32W | 48W | 120W |
| Control | On-Off / DMX 512 | On-Off / DMX 512 | On-Off / DMX 512 | On-Off / DMX 512 | On-Off / DMX 512 |
| Address Setting | Auto/Manual | Auto/Manual | Auto/Manual | Auto/Manual | Auto/Manual |
| DMX Channels | 1 - 3 | 1 - 3 | 1 - 3 | 1 - 3 | 1 - 3 |
| Housing | Powder coated in Gray | Powder coated in Gray | Powder coated in Gray | Powder coated in Gray | Powder coated in Gray |
| Accessories | Angled glare shield<br>Glare shield | Angled glare shield<br>Glare shield | Angled glare shield<br>Glare shield | Angled glare shield<br>Glare shield | Angled glare shield<br>Glare shield |
| Cable entry | Bottom | Bottom | Bottom | Bottom | Bottom |
| Operating Temperature | -20° to 50°C | -20° to 50°C | -20° to 50°C | -20° to 50°C | -20° to 50°C |
| Storage Temperature | -40° to 80°C | -40° to 80°C | -40° to 80°C | -40° to 80°C | -40° to 80°C |
| IP | IP65 | IP65 | IP65 | IP65 | IP65 |
| Certificate | CE/ROHS | CE/ROHS | CE/ROHS | CE/ROHS | CE/ROHS |

professional LED display

# Flood Light





ACCESSORIES



### FL800303 FLOOD LIGHT

SIZE: 3.14"x 3.14"x4.84"
(80x80x123mm)
ORDER CODE: UNIFL800303

### FL960903 FLOOD LIGHT

SIZE: 3.77"x3.77"x4.33"x5.90"
(96x96xd110xh150mm)
ORDER CODE: UNIFL960903

### FL1351603 FLOOD LIGHT

SIZE: 5.31"x5.31"x5.51"x8.46"
(135x135xd140xh215mm)
ORDER CODE: UNIFL1351603

### FL1702403 FLOOD LIGHT


SIZE: 6.69"x6.69"x5.39"x9.64"
(170x170xd137xh245mm)
ORDER CODE: UNIFL1702403


### FL2136003 FLOOD LIGHT


SIZE: 8.38"x8.38"x7.48"x13.58"
(213x213xd190xh345mm)
ORDER CODE: UNIFL2136003


## SPECIFICATION


| | FL1700904 | FL2131604 |
|---|---|---|
| Size | 170x170xd137xh245mm | 213x213xh260mm |
| Diffuser | Clear Tempered Glass | Clear Tempered Glass |
| Color | RGBW 4in1 | RGBW 4in1 |
| Led | High Power LED | High Power LED |
| Led Q.ty | 9 PCS | 16 PCS |
| Beam angle | 5°-18°- 30°- 40° | |
| Voltage | 85-260V DC | 85-260V DC |
| Power | 48W | 120W |
| Control | DMX 512 | DMX 512 |
| Address Setting | Auto/Manual | Auto/Manual |
| DMX Channels | 4 | 4 |
| Housing | Powder coated in Gray | Powder coated in Gray |
| Accessories | Angled glare shield<br>Glare shield | Angled glare shield<br>Glare shield |
| Cable entry | Bottom | Bottom |
| Operating Temperature | -20° to 50°C | -20° to 50°C |
| Storage Temperature | -40° to 80°C | -40° to 80°C |
| IP | IP65 | IP65 |
| Certificate | CE/ROHS | CE/ROHS |



### FL1700904 FLOOD LIGHT

SIZE: 6.69"x6.69"x5.39"x9.64"
(170x170xd137xh245mm)
ORDER CODE: UNIFL1700904

### FL2131604 FLOOD LIGHT

SIZE: 8.38"x8.38"x10.23"
(213x213x260mm)
ORDER CODE: UNIFL2131604

## ACCESSORIES




professional LED display

# Flood Light

## SPECIFICATION

| | FL1100603 | FL1700903 | FL2061803 | FL2403603 | FL2405403 | FL2806003 |
|---|---|---|---|---|---|---|
| Size | 110xd98xh146mm | 170xd122xh215mm | 206xd145xh245mm | 240xd190xh380mm | 240xd190xh380mm | 280xd215xh370mm |
| Diffuser | Clear Tempered Glass | Clear Tempered Glass | Clear Tempered Glass | Clear Tempered Glass | Clear Tempered Glass | Clear Tempered Glass |
| Color | White 2700K-5770K/ RGB | White 2700K-5770K/ RGB | White 2700K-5770K/ RGB | White 2700K-5770K/ RGB | White 2700K-5770K/ RGB | White 2700K-5770K/ RGB |
| Led | High Power LED | High Power LED | High Power LED | High Power LED | High Power LED | High Power LED |
| Led Q.ty | 6 PCS | 9 PCS | 16 PCS | 24 PCS | 60 PCS | 60 PCS |
| Beam angle | 10°-15°-22°-30°-50°-66°-83° | | | | | |
| Voltage | 24V DC | 85-260V DC | 85-260V DC | 85-260V DC | 85-260V DC | 85-260V DC |
| Power | 6W | 18W | 36W | 72W | 108W | 120W |
| Control | On-Off / DMX 512 | On-Off / DMX 512 | On-Off / DMX 512 | On-Off / DMX 512 | On-Off / DMX 512 | On-Off / DMX 512 |
| Address Setting | Auto/Manual | Auto/Manual | Auto/Manual | Auto/Manual | Auto/Manual | Auto/Manual |
| DMX Channels | 1 - 3 | 1 - 3 | 1 - 3 | 1 - 3 | 1 - 3 | 1 - 3 |
| Housing | Powder coated in Gray | Powder coated in Gray | Powder coated in Gray | Powder coated in Gray | Powder coated in Gray | Powder coated in Gray |
| Accessories | Angled glare shield Glare shield | Angled glare shield Glare shield | Angled glare shield Glare shield | Angled glare shield Glare shield | Angled glare shield Glare shield | Angled glare shield Glare shield |
| Cable entry | Bottom | Bottom | Bottom | Bottom | Bottom | Bottom |
| Operating Temperature | -20° to 50°C | -20° to 50°C | -20° to 50°C | -20° to 50°C | -20° to 50°C | -20° to 50°C |
| Storage Temperature | -40° to 80°C | -40° to 80°C | -40° to 80°C | -40° to 80°C | -40° to 80°C | -40° to 80°C |
| IP | IP65 | IP65 | IP65 | IP65 | IP65 | IP65 |
| Certificate | CE/ROHS | CE/ROHS | CE/ROHS | CE/ROHS | CE/ROHS | CE/ROHS |








## ACCESSORIES











### FL1100603 FLOOD LIGHT

SIZE: 4.33"x 3.85"x5.74"(110xd98xh146mm)
ORDER CODE: UNIFL1100603

### FL1700903 FLOOD LIGHT

SIZE: 6.69"x4.80"x8.46"(170xd122xh215mm)
ORDER CODE: UNIFL1700903

### FL2061803 FLOOD LIGHT

SIZE: 8.11"x5.7"x9.64"(206xd145xh245mm)
ORDER CODE: UNIFL2061803

### FL2403603 FLOOD LIGHT

SIZE: 9.44"x7.48"x14.96"(240xd190xh380mm)
ORDER CODE: UNIFL2403603

### FL2405403 FLOOD LIGHT

SIZE: 9.44"x7.48"x14.96"(240xd190xh380mm)
ORDER CODE: UNIFL2405403

### FL2806003 FLOOD LIGHT

SIZE: 11.02"x8.46"x14.56"(280xd215xh370mm)
ORDER CODE: UNIFL2806003

# Flood Light

## FEATURES

- Flood Light Series is designed for architectural facede, bridge and so on.
- High Efficiency light output and uniform beam with professional lense.
- Top brand silicone  for better heatconduction, strong temperature withstand and perfect waterproof performance.
- Led color always keep same brightness after long distance power supply.
- The communication between lights are synchronized perfectly under support of Artnet Controller.
- Standard DMX512 control protocol (Max 44frames/second).
- Save 40% power with more efficient power management design.
- Protections: short circuit, over current, over voltage and over temperature.

FL3504803 – FL3509603 – FL57510003 – FL57520003
Flood Light



FL4858401A – FL4868401B
Flood Light





## SPECIFICATION

| | FL3504803 | FL3509603 | FL57510003 | FL57520003 | FL4858401A | FL4868401B |
|---|---|---|---|---|---|---|
| Size | 350x150xh201mm | 350x122xh210mm | 575x150xh210mm | 575x370xh210mm | 480xh300mm | 480xh300mm |
| Diffuser | Clear Tempered Glass | Clear Tempered Glass | Clear Tempered Glass | Clear Tempered Glass | Clear | Clea |
| Color | White 2700K-5770K/ RGB | White 2700K-5770K/ RGB | White 2700K-5770K/ RGB | White 2700K-5770K/ RGB | White 2700K-5770K | White 2700K-5770K |
| Led | High Power LED | High Power LED | High Power LED | High Power LED | High Power LED | High Power LED |
| Led Q.ty | 48 PCS | 96 PCS | 100 PCS | 200 PCS | 84 PCS | 84 PCS |
| Beam angle | 10°-15°-22°-30°-50°-66°-83° | | | | 5°-10°-20°-30°-60° | |
| Voltage | 85-260V DC | 85-260V DC | 85-260V DC | 85-260V DC | 100-260V DC | 100-260V DC |
| Power | 100W | 200W | 200W | 400W | 250W | 500W |
| Control | On-Off / DMX 512 | On-Off / DMX 512 | On-Off / DMX 512 | On-Off / DMX 512 | On-Off | On-Off |
| Address Setting | Auto/Manual | Auto/Manual | Auto/Manual | Auto/Manual | - | - |
| DMX Channels | 1 - 3 | 1 - 3 | 1 - 3 | 1 - 3 | - | - |
| Housing | Powder coated in Gray | Powder coated in Gray | Powder coated in Gray | Powder coated in Gray | Powder coated in Gray | Powder coated in Gray |
| Accessories | Angled glare shield Glare shield | Angled glare shield Glare shield | Angled glare shield Glare shield | Angled glare shield Glare shield | Angled glare shield Glare shield | Angled glare shield Glare shield |
| Cable entry | Bottom | Bottom | Bottom | Bottom | Bottom | Bottom |
| Operating Temperature | -20° to 50°C | -20° to 50°C | -20° to 50°C | -20° to 50°C | -20° to 50°C | -20° to 50°C |
| Storage Temperature | -40° to 80°C | -40° to 80°C | -40° to 80°C | -40° to 80°C | -40° to 80°C | -40° to 80°C |
| IP | IP65 | IP65 | IP65 | IP65 | IP65 | IP65 |
| Certificate | CE/ROHS | CE/ROHS | CE/ROHS | CE/ROHS | CE/ROHS | CE/ROHS |

professional LED display

# Flood Light









## ACCESSORIES











### FL3504803 FLOOD LIGHT

SIZE: 13.77"x 5.9"x8.26"(350x150xh210mm)
ORDER CODE: UNIFL3504803

### FL3509603 FLOOD LIGHT

SIZE: 13.77"x4.80"x8.26"(350x122xh210mm)
ORDER CODE: UNIFL3509603

### FL57510003 FLOOD LIGHT

SIZE: 22.63"x5.9"x8.26"(575x150xh210mm)
ORDER CODE: UNIFL57510003

### FL57520003 FLOOD LIGHT

SIZE: 22.63"x14.76"x8.26"(575x370xh210mm)
ORDER CODE: UNIFL57520003


### FL4858401A FLOOD LIGHT

SIZE: 18.89"x11.81"(480xh300mm)
ORDER CODE: UNIFL4858401A

### FL4868401B FLOOD LIGHT

SIZE: 18.89"x11.81"(480xh300mm)
ORDER CODE: UNIFL4868401B

UNITECH DIGITAL MEDIA ultra professional LED display company



# Cable& Connector

UNITECH DIGITAL MEDIA

# Cable & Connector

## IP67 CONNECTOR PUSH LOCK



4PIN Extension Cable 67E4M4F
ORDER CODE: UNICPL67EM4F



T Connector for Signal&Power 67T5XM4F2M
ORDER CODE: UNICPL67T5XM4F2M



T Connector for Power 67T4M4F2M
ORDER CODE: UNICPL67T4M4F2M



2PIN Power Cable 67E2FB
ORDER CODE: UNICPL67E2FB

## IP67 CONNECTOR SCREW LOCK



2PIN Power Cable 67E2FB
ORDER CODE: UNICSL67E2FB



T Connector for Signal&Power 67T5XM4F2M
ORDER CODE: UNICSL67T5XM4F2M



T Connector for Power 67T4M4F2M
ORDER CODE: UNICSL67T4M4F2M

## IP65 CONNECTOR SCREW LOCK



2PIN Power Cable 65E2FB
ORDER CODE: UNICSL65E2FB



T Connector for Signal&Power 65T5XM4F2M
ORDER CODE: UNICSL65T5XM4F2M



T Connector for Power 65T4M4F2M
ORDER CODE: UNICSL65T4M4F2M



T Connector for LED Fixture 65T4M4F4F
ORDER CODE: UNICSL65T4M4F4F

## NO WATERPROOF CONNECTOR



5PIN XLR Female – CD – XLR5F
ORDER CODE: UNINWCXLR5F



5PIN XLR Male – CD – XLR5M
ORDER CODE: UNINWCXLR5M



3PIN XLR Female – CD – XLR3F
ORDER CODE: UNINWCXLR3F



3PIN XLR Male – CD – XLR3M
ORDER CODE: UNIAC67E2FB



T Connector for Signal&Power
NWT5XM4F2M
ORDER CODE: UNINWT5XM4F2M



4PIN Extension Cable NWE4M4F
ORDER CODE: UNINWE4M4F



Signal Cable NWE5XM3SF
ORDER CODE: UNINWE5XM3SF